

In re: Ik-Soo Lee
Serial No.: 08/847,017
Filed: May 1, 1997
Page 2 of 17



RECEIVED

MAR 11 1999

TECHNOLOGY CENTER 3700

Ar
5 wherein the fixing means includes a first corner, and
a second corner which is **[remote]** spaced farther from the
means for receiving a display device light source **[relative**
to] than the first corner is spaced from the means for
receiving a display device light source; and

wherein the first corner is angled and the second
corner is rounded.

3
4. (Amended) A mold frame according to Claim 2 wherein the groove
is **[free of sharp angles]** entirely rounded.

5. (Amended) A light guide panel for a display device comprising:
[a light guide plate; and]
a light guide projection which extends from the
light guide **[plate]** panel, the light guide projection
including at least one rounded corner and at least one
angled corner, the at least one rounded corner operative to
reduce concentration of light in the light guide projection.

Please cancel Claims 6 and 7.

8. (Amended) A backlight unit for a display device comprising:
a mold frame which includes a groove having at least
one rounded corner; **[and]**
a light source on the mold frame and operative to
provide light; and
a light guide panel **[mounted]** on the mold frame in
spaced apart relation from the light source, including a light
guide projection **[mounted]** in the groove **[and]**, the light

B1
1-0

guide projection having at least one rounded corner corresponding to the at least one rounded corner of the mold frame groove, the rounded corners of the mold frame groove and the light guide projection being cooperative to maintain the light guide panel and the light source in spaced relation, the at least one rounded corner of the light guide projection being operative to reduce concentration of the light in the light guide projection.

15

6
9.
comprising:

(Amended) A backlight unit according to Claim 8, [further

a light source mounted on the mold frame, in spaced apart relation from the light guide panel;]

5

wherein the mold frame groove and the light guide panel both include a first corner, and a second corner which is [remote] spaced farther from the light source [relative to] than the first corner is spaced from the light source; [and]

10

wherein the first [corner is] corners are angled and the second [corner is] corners are rounded; and

15

wherein the first corner of the light guide panel is disposed adjacent the first corner of the mold frame groove and the second corner of the light guide panel is disposed adjacent the second corner of the mold frame groove.

7
10. (Amended) A backlight unit according to Claim 8, wherein the groove and light guide projection are both [free of sharp angles] entirely rounded.

12

9

11. (Amended) A flat panel display device comprising:
a mold frame which includes a groove having at
least one rounded corner;

A7

5

a light source mounted on the mold frame and
operative to provide light;

10

a light guide panel on the mold frame in spaced
apart relation from the light source, including a light guide
projection mounted in the groove **[and]**, the light guide
projection having at least one rounded corner
corresponding to the at least one rounded corner of the
mold frame groove, the rounded corners of the mold frame
groove and the light guide projection being cooperative to
maintain the light guide panel and the light source in
spaced relation, the at least one rounded corner of the light
guide projection being operative to reduce concentration of
the light in the light guide projection;

15

**[a light source on the mold frame, in spaced
apart relation from the light guide panel; and**

20

an array of display elements] a display panel
disposed on the light guide panel [, opposite the mold
frame] and positioned such that the light guide panel is
interposed between the mold frame and the display panel.

10

12. (Amended) A flat panel display device according to
Claim 11 further comprising a diffuser between the light guide panel and
the **[array of display elements]** display panel.

11

13. (Amended) A flat panel display device according to Claim 12
further comprising a printed circuit board on the mold frame, the printed circuit board
[including a plurality of integrated circuits which are] being electrically connected
to the **[array of display elements]** display panel.

10

13

12
14.

(Amended) A flat panel display device according to Claim 11:

wherein the mold frame groove and light guide panel both include a first corner, and a second corner which is [remote] spaced farther from the light source [relative to] than the first corner is spaced from the light source; [and]

wherein the first [corner is] corners are angled and the second [corner is] corners are rounded; and

wherein the first corner of the light guide panel is disposed adjacent the first corner of the mold frame groove and the second corner of the light guide panel is disposed adjacent the second corner of the mold frame groove.

15.

(Amended) A flat panel display device according to Claim 11

wherein the groove and light guide projection are both [free of sharp angles] entirely rounded.

Please add the following new claims:

--16.

The light guide panel according to Claim 5 wherein the light guide panel defines a peripheral edge, the peripheral edge being formed in part by the light guide projection.

8
17.

The backlight unit according to Claim 8 wherein the light guide panel defines a peripheral edge, the peripheral edge being formed in part by the light guide projection.

14
18.

The flat panel display device according to Claim 11 wherein the light guide panel defines a peripheral edge, the peripheral edge being formed in part by the light guide projection.--

14